

HYTSU® T&U®



✓ 100 SERIES

CE

1.0 - 1.5 TON

HEAVY DUTY HAND STACKER

XHY 10

XKJ 10/15



◀ **XHY1016**
XHY1030



XKJ1016/1030 ▶
XKJ1516/1530

STANDARD SPECIFICATIONS

characteristics	1	Manufacturer		Unit	HYTSU GROUP			
	2	Model			Single mast		2-Stage mast	
					XHY1016	XKJ1016	XHY1030	XKJ1030
	3	Load Capacity	kg/lb	1000 / 2200	1000 / 2200	1000 / 2200	1000 / 2200	
					1500 / 3300		1500 / 3300	
4	Load Center	mm/inch	600 / 23.6	600 / 23.6	600 / 23.6	600 / 23.6		
				500 / 19.7		500 / 19.7		
5	Control Type		mm/inch	Manual				
dimensions	6	Standard Lifting Height		mm/inch	1600 / 63		3000 / 118.1	
	7	Fork Size	L*W*T	mm/inch	1130*160*50			
	8	Fork Overall Width		mm/inch	540 / 21.3	340-730/13.4-28.7 (adjustable)	540 / 21.3	340-730/13.4-28.7 (adjustable)
	9	Overall Length		mm/inch	1600 / 63	1830 / 72	1600 / 63	1830 / 72
	10	Overall Width		mm/inch	650 / 25.6		1430 / 56.3	
	11	Mast Height; Mast Lowered		mm/inch	2055 / 80.9		1955 / 77	
	12	Overall Height; Fork Raised		mm/inch	1950 / 76.8		3350 / 131.9	
	13	Fork Lowered		mm/inch	88 / 3.5	65 / 2.6	88 / 3.5	65 / 2.6
	14	Handle Height		mm/inch	1245 / 49			
	15	Leg Width		mm/inch	485 / 19.1	1430 / 56.3	485 / 19.1	1430 / 56.3
	16	Leg Length		mm/inch	1020 / 40.2	1060 / 41.7	1020 / 40.2	1060 / 41.7
	17	Turning Radius(Outside)		mm/inch	1170 / 46.1	1210 / 47.6	1170 / 46.1	1210 / 47.6
	18	Min.ground Clearance		mm/inch	24 / 0.9	45 / 1.9	24 / 0.9	45 / 1.9
19	Basic Right Angle Stacking Aisle Width (Add load length and clearance)		mm/inch	1290 / 50.8	1780 / 70.1	1290 / 50.8	1780 / 70.1	
performance	20	Gradeability	With load	%	4			
			Without load		11			
brake and wheels	21	Wheels	Front/Rear		2/2			
			Front		Φ78*90			
			Rear		Φ150*50			
22	Axle Base		mm/inch	1100 / 43.3				
23	Brake			Foot Brake				
Weight	24	Total Weight	kg/lb	246 / 542	312 / 687	298 / 656	364 / 802	
					320 / 705		372 / 819	

* Notes: Products and specifications are subject to change without notice.